Technical Data



CCL 100 CONTACT CLEANER LUBRICANT



CCL 100 is a highly efficient switch and contact cleaner. It offers a combination of high purity electrical cleaning and mechanical lubrications for contacts, switches and relays.

APPLICATIONS

Removes grease, tarnish, oxidisation and other contamination from contact surfaces and leaves a protective conductive lubricating film.

Cuts voltage drop between contacts by increasing the surface area and reducing resistance. The residual film resists drying and the attraction of dust. Eliminates contact bounce and stops the damage which can be caused by arcing between contacts. Improves the current flow and protects against friction.

Apply directly onto the components to be treated. Do not use on live electrical equipment. After spraying, always leave for at least 4/5 minutes to allow dispersal of solvent vapours, before operating the equipment.

TECHNICAL DATA

Appearance : Clear liquid

Odour : Solvent

SG @ 250C : 0.7

Pressure @ 25OC : 3.5 Bar

Discharge Rate : 0.93 g/sec

Temperature Range : Operational up to 150OC

Solubility : Soluble in hydrocarbon solvents, insoluble in water

Recommended Solvents : Aeroklene 50 or Coldklene 110

Flammability : Classified as extremely flammable under CHIP

Regulations

Flashpoint : Not applicable in sealed aerosol

Packaging : 200ml aerosol

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50° C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRA

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644

Web: www.ambersil.com Email: sales.uk@crcind.com