according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) D-321 R SPRAY

Product code : 00000000001659766, 00000000001659766

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricants and lubricant additives

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Manufacturer or supplier's

details

: 65091

Telephone : English Tel: +49 611237507

Deutsch Tel: +49 611237500 Français Tel: +32 64511149 Italiano Tel: +32 64511170 Español Tel: +32 64511163

E-mail address of person responsible for the SDS

: sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350 Dow Corning (Wiesbaden 24h) Tél: +49 61122158 Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H373 May cause damage to organs through pro-

longed or repeated exposure.

H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated

area.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrodesulfurized heavy

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Molybdenum disulfide

aerosol

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Naphtha (petroleum), hydrodesul-	64742-82-1	Flam. Liq. 3; H226	>= 2.5 - < 10
furized heavy	265-185-4	STOT SE 3; H336	
		STOT RE 1; H372	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Polybutyl titanate	9022-96-2	Flam. Liq. 3; H226 Eye Irrit. 2; H319	>= 3 - < 10
Zinc oxide	1314-13-2 215-222-5 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.1 - < 0.25

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: None known.

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides Sulphur oxides

5.3 Advice for firefighters

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety

practice.

Keep away from water. Protect from moisture.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep

cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases Explosives Gases

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

7.3 Specific end use(s)

Specific use(s) : For further information regarding the use of silicones / organic

oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the

Dow Corning customer service group.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
n-Butyl acetate	123-86-4	of exposure) TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
Molybdenum sul- fide	1317-33-5	TWA	10 mg/m3 (Molybdenum)	GB EH40
		STEL	20 mg/m3 (Molybdenum)	GB EH40
Graphite Further information	7782-42-5	TWA (inhalable dust)	10 mg/m3	GB EH40
	fractions of ai in accordance sampling and COSHH defin kind when pre 8-hour TWA of This means the above these I posure to the contain particular of any particular pody response HSE distinguible and respinaterial that a available for of to the fraction definitions and contain compishould be cora figure three	`		
Further information			espirable dust and inhalable ill be collected when samplin	



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	960 mg/m3
	Workers	Inhalation	Acute local effects	960 mg/m3
	Workers	Inhalation	Long-term systemic effects	480 mg/m3
	Workers	Inhalation	Long-term local ef- fects	480 mg/m3
	Consumers	Inhalation	Acute systemic effects	859.7 mg/m3
	Consumers	Inhalation	Acute local effects	859.7 mg/m3
	Consumers	Inhalation	Long-term systemic effects	102.34 mg/m3
	Consumers	Inhalation	Long-term local effects	102.34 mg/m3
Graphite	Consumers	Inhalation	Long-term local effects	0.3 mg/m3



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

	Consumers	Ingestion	Long-term systemic effects	813 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	1.2 mg/m3
Zinc oxide	Workers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0.83 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-Butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Intermittent use/release	0.36 mg/l
	Sewage treatment plant	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.0981 mg/kg
	Soil	0.0903 mg/kg
Zinc oxide	Fresh water	20.6 μg/l
	Marine water	6.1 µg/l
	Sewage treatment plant	52 μg/l
	Fresh water sediment	117.8 mg/kg
	Marine sediment	56.5 mg/kg
	Soil	35.6 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety goggles

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Hand protection

Material : Impervious gloves

Flame retardant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Skin and body protection : Wear the following personal protective equipment:

Flame retardant antistatic protective clothing.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Aerosol containing a dissolved gas

Colour : black

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Relative density : 1.05

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon con-

tact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

Water

10.6 Hazardous decomposition products

Contact with water or humid : Butan-1-ol

air

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 13.1 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: Based on data from similar materials

Assessment: Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Zinc oxide: Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Remarks: Based on data from similar materials

Polybutyl titanate:

Result: Irritation to eyes, reversing within 21 days

Zinc oxide: Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Inhalation

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity- As-

sessment

: Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rat

Application Route: inhalation (vapour)

Exposure time: 13 weeks

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Hamster

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Target Organs: Central nervous system

Assessment: Causes damage to organs through prolonged or repeated exposure.

Zinc oxide:

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rat NOAEL: 2.34 mg/l LOAEL: 4.67 mg/l

Application Route: inhalation (vapour)

Exposure time: 6 Months

Method: OECD Test Guideline 413

Remarks: Based on data from similar materials

Zinc oxide:

Species: Rat NOAEL: 1.5 mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 3 Months

Method: OECD Test Guideline 413

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

Version Revision Date: SDS Number: Date of last issue: 30.10.2015 10.12.2015 1368875-00007 Date of first issue: 17.02.2015 1.6

Aspiration toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

: Target Organs: Central nervous system Inhalation

Symptoms: Dizziness, Headache, Neurological disorders

SECTION 12: Ecological information

12.1 Toxicity

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 10 - 30 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): 10 - 22 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 4.6 - 10

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR: 0.097 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Zinc oxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 330 - 780 μg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 6.9 - 16.2 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 136 μg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 24 µg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

Toxicity to bacteria

icity)

: EC50 : 5.2 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

: NOEC: 199 μg/l Exposure time: 30 d

> Species: Oncorhynchus mykiss (rainbow trout) Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: NOEC: 37 μg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

: 1

12.2 Persistence and degradability

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Biodegradability : Result: Readily biodegradable

Biodegradation: 74.7 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Polybutyl titanate:

Biodegradability : Result: Not readily biodegradable.

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

12.3 Bioaccumulative potential

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Based on data from similar materials

Zinc oxide:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 177

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Do not burn.

If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2.1
ADR : 2.1
RID : 2.1
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
18	Liquefied extremely flam- mable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in	2,500 t	25,000 t

DOW CORNING

MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

points (a) to (d)

Other regulations : Take note of Dir 94/33/EC on the protection of young people

at work.

Take note of Directive 92/85/EEC regarding maternity protec-

tion or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applica-

ble.

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or

exempted from listing on the TSCA Inventory of Chemical

Substances.

PICCS : All ingredients listed or exempt.

KECI : All ingredients listed, exempt or notified.

IECSC : All ingredients listed or exempt.

AICS : All ingredients listed or exempt.

REACH : All ingredients (pre-)registered or exempt.

ENCS/ISHL : Some components are not listed or not identified on

ENCS/ISHL.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the Ca-

nadian Domestic Substances List (DSL).

TCSI : All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H319 : Causes serious eye irritation.

H336 : May cause drowsiness or dizziness.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

Full text of other abbreviations

Aquatic Acute : Acute aquatic toxicity
Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Lig. : Flammable liquids

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x\% response; ELx - Loading rate associated with x\% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sheet

Sources of key data used to compile the Safety Data

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D-321 R SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.10.2015

 1.6
 10.12.2015
 1368875-00007
 Date of first issue: 17.02.2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN