according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) D SPRAY

Product code : 00000000001623605, 000000000001623605

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricants and lubricant additives

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Manufacturer or supplier's

details

: 65091

Telephone : English Tel: +49 611237507

Deutsch Tel: +49 611237500 Français Tel: +32 64511149 Italiano Tel: +32 64511170 Español Tel: +32 64511163

E-mail address of person

responsible for the SDS

: sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350 Dow Corning (Wiesbaden 24h) Tél: +49 61122158 Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated

area.

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Calcium hydroxide

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Hydrocarbon aerosol propellant

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Naphtha (petroleum), hydrotreated heavy	64742-48-9 265-150-3	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Calcium hydroxide	1305-62-0 215-137-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 10 - < 20

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

: Carbon oxides Metal oxides

Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid inhalation of vapour or mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with

the particular national regulations. Do not pierce or burn, even

after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases Explosives

7.3 Specific end use(s)

Specific use(s) : For further information regarding the use of silicones / organic

oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the

Dow Corning customer service group.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Calcium hydroxide	1305-62-0	TWA	5 mg/m3	91/322/EEC
Further information	Existing scientific data on health effects appear to be particularly limited, Indicative			
		TWA	5 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium hydroxide	Workers	Inhalation	Acute local effects	4 mg/m3
	Workers	Inhalation	Long-term local effects	1 mg/m3
	Consumers	Inhalation	Acute local effects	4 mg/m3
	Consumers	Inhalation	Long-term local effects	1 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium hydroxide	Fresh water	0.49 mg/l
	Marine water	0.32 mg/l
	Intermittent use/release	0.49 mg/l
	Sewage treatment plant	3 mg/l
	Soil	1080 mg/kg

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D SPRAY

Version Revision Date: SDS Number: Date of last issue: 09.02.2015 1296323-00002 Date of first issue: 09.02.2015 14.10.2015 1.1

İ	1	1	
Distillates (petroleum), solvent	Oral	9.33 mg/kg	
,	0.0.	c.ccgg	
refined heavy naphthenic			

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

If splashes are likely to occur, wear:

Face-shield

Hand protection

Material Impervious gloves

Flame retardant gloves

Remarks Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Skin and body protection Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tial.

Wear the following personal protective equipment: Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

: Use respiratory protection unless adequate local exhaust ven-Respiratory protection

tilation is provided or exposure assessment demonstrates that

exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Aerosol containing a dissolved gas

Colour : white, translucent

Odour : solvent-like

Odour Threshold : No data available



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0.69

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for

formaldehyde.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Calcium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 425

Assessment: The substance or mixture has no acute oral tox-

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

icity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species: Rabbit

Result: Mild skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

Calcium hydroxide:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Remarks: Based on data from similar materials

Calcium hydroxide:

Species: Rabbit

Method: OECD Test Guideline 405 Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Components:

Naphtha (petroleum), hydrotreated heavy:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Germ cell mutagenicity- As-

sessment

: Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Calcium hydroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species: Rat

Application Route: inhalation (vapour)

Exposure time: 105 weeks

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Calcium hydroxide:

Species: Rat

Application Route: Ingestion Exposure time: 104 weeks

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop- : Test Type: Embryo-foetal development

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

ment Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Calcium hydroxide:

Effects on foetal develop- : Test Type: Embryo-foetal development

ment Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Assessment: May cause drowsiness or dizziness.

Calcium hydroxide:

Assessment: May cause respiratory irritation.

Remarks: The substance is inextricably bound in the product and therefore does not contribute

to a dust inhalation hazard.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Naphtha (petroleum), hydrotreated heavy:

Species: Rat

NOAEL: 10,186 mg/m3

Application Route: inhalation (vapour)

Exposure time: 13 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Naphtha (petroleum), hydrotreated heavy:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l

Exposure time: 96 h

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Calcium hydroxide:

Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457

mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 49.1 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC10 (Pseudokirchneriella subcapitata (green algae)): 79.22

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to bacteria : EC50 : 300.4 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: NOEC: 32 mg/l Exposure time: 14 d

12.2 Persistence and degradability

Components:

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Naphtha (petroleum), hydrotreated heavy:

Biodegradability : Result: Readily biodegradable

Biodegradation: 89 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Do not burn.

If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2.1
ADR : 2.1
RID : 2.1
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

RID

Environmentally hazardous : no

MDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident bazards involving dangerous substances

major-accident hazards involving	Quantity 1	Quantity 2	
P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t
18	Liquefied extremely flam- mable gases (including LPG) and natural gas	50 t	200 t

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

Other regulations : Take note of Dir 94/33/EC on the protection of young people

at work.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applica-

ble

The components of this product are reported in the following inventories:

REACH : All ingredients (pre-)registered or exempt.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

PICCS : All ingredients listed or exempt.

Additional regulatory information

9-Octadecenyl-13-docosenate 17673-56-2

TSCA clearance for manufacture, import, processing, or use of this product is based on a low volume exemption from the Inventory listing requirements of TSCA (40 CFR 723.50(c) (1)). For activities regulated by TSCA, the following conditions apply: The LVE substance contained in the product may only be used as a lubricant. The low volume exemption specifies that processors and industrial users of this product will control exposure by using pumping and application apparatus for transfer and use whenever possible, and will landfill spent product containers.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic

Asp. Tox.

Eye Dam.

Flam. Liq.

Skin Irrit.

: Chronic aquatic toxicity

: Aspiration hazard

: Serious eye damage

Flammable liquids

: Skin irritation

STOT SE : Specific target organ toxicity - single exposure

91/322/EEC : Europe. Commission Directive 91/322/EEC on establishing

indicative limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

91/322/EEC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN

according to Regulation (EC) No. 1907/2006



MOLYKOTE(R) D SPRAY

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09.02.2015

 1.1
 14.10.2015
 1296323-00002
 Date of first issue: 09.02.2015