

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOLYKOTE(R) G-RAPID PLUS PASTE  
Product code : 000000000001909126, 000000000001909126

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricants and lubricant additives

#### 1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.  
rue Jules Bordet - Parc Industriel - Zone C  
B-7180 Seneffe  
Telephone : English Tel: +49 611237507  
Deutsch Tel: +49 611237500  
Français Tel: +32 64511149  
Italiano Tel: +32 64511170  
Español Tel: +32 64511163  
E-mail address of person responsible for the SDS : sdseu@dowcorning.com

#### 1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350  
Dow Corning (Wiesbaden 24h) Tél: +49 61122158  
Dow Corning (Seneffe 24h) Tel: +32 64 888240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1      H318: Causes serious eye damage.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements : **Prevention:**  
P280 Wear eye protection/ face protection.

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

**Response:**

P305 + P351 + P338 + P310    IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:  
Calcium hydroxide

### 2.3 Other hazards

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Inorganic and organic compounds  
Mixture

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27	Asp. Tox. 1; H304	>= 30 - < 50
Calcium hydroxide	1305-62-0 215-137-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 20 - < 30

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.



## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

---

If swallowed : If easy to do, remove contact lens, if worn.  
Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye damage.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Metal oxides  
Sulphur oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

---

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 07.10.2015
1.4	12.11.2015	844350-00005	Date of first issue: 26.11.2014

---

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice.  
Keep container tightly closed.  
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Keep tightly closed.  
Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents

**MOLYKOTE(R) G-RAPID PLUS PASTE**

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

**7.3 Specific end use(s)**

Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Molybdenum sulfide	1317-33-5	TWA	10 mg/m <sup>3</sup> (Molybdenum)	GB EH40
		STEL	20 mg/m <sup>3</sup> (Molybdenum)	GB EH40
Calcium hydroxide	1305-62-0	TWA	5 mg/m <sup>3</sup>	91/322/EEC
Further information	Existing scientific data on health effects appear to be particularly limited, Indicative			
		TWA	5 mg/m <sup>3</sup>	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Graphite	7782-42-5	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any			

**MOLYKOTE(R) G-RAPID PLUS PASTE**

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

	<p>kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>
--	--

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium hydroxide	Workers	Inhalation	Acute local effects	4 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	1 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	4 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	1 mg/m <sup>3</sup>
Graphite	Consumers	Inhalation	Long-term local effects	0.3 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	813 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	1.2 mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
Calcium hydroxide	Fresh water	0.49 mg/l
	Marine water	0.32 mg/l
	Intermittent use/release	0.49 mg/l
	Sewage treatment plant	3 mg/l
	Soil	1080 mg/kg

**8.2 Exposure controls**

**Engineering measures**

Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 07.10.2015
1.4	12.11.2015	844350-00005	Date of first issue: 26.11.2014

### Personal protective equipment

- Eye protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
If splashes are likely to occur, wear:  
Face-shield
- Hand protection  
Material : Impervious gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapour type (A-P)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : paste
- Colour : black
- Odour : slight
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : > 200.0 °C  
Method: closed cup
- Evaporation rate : Not applicable

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 07.10.2015
1.4	12.11.2015	844350-00005	Date of first issue: 26.11.2014

---

Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	No data available
Relative density	:	1.4
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Molecular weight	:	No data available
------------------	---	-------------------

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde.
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

---

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

##### **Calcium hydroxide:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 425  
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials

#### Components:

##### **White mineral oil (petroleum):**

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

---

Species: Rabbit  
Result: No skin irritation

**Calcium hydroxide:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: Skin irritation

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Components:**

**White mineral oil (petroleum):**

Species: Rabbit  
Result: No eye irritation

**Calcium hydroxide:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: Irreversible effects on the eye

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
Respiratory sensitisation: Not classified based on available information.

**Components:**

**White mineral oil (petroleum):**

Test Type: Buehler Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**White mineral oil (petroleum):**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Calcium hydroxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

---

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **White mineral oil (petroleum):**

Species: Rat  
Application Route: Ingestion  
Exposure time: 24 Months  
Result: negative

#### **Calcium hydroxide:**

Species: Rat  
Application Route: Ingestion  
Exposure time: 104 weeks  
Result: negative  
Remarks: Based on data from similar materials

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **White mineral oil (petroleum):**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Skin contact  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### **Calcium hydroxide:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **Calcium hydroxide:**

Assessment: May cause respiratory irritation.  
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

### **STOT - repeated exposure**

Not classified based on available information.

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

### Repeated dose toxicity

#### Components:

##### **White mineral oil (petroleum):**

Species: Rat  
LOAEL: > 160 mg/kg  
Application Route: Ingestion  
Exposure time: 90 Days

Species: Rat  
LOAEL: >= 1 mg/l  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 4 Weeks  
Method: OECD Test Guideline 412

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### **White mineral oil (petroleum):**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **White mineral oil (petroleum):**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC: 1,000 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,000 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)
- ##### **Calcium hydroxide:**
- Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

---

- Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 49.1 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : EC10 (Pseudokirchneriella subcapitata (green algae)): 79.22 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50 : 300.4 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l  
Exposure time: 14 d

### 12.2 Persistence and degradability

#### Components:

#### **White mineral oil (petroleum):**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste han-



## MOLYKOTE(R) G-RAPID PLUS PASTE

Version 1.4      Revision Date: 12.11.2015      SDS Number: 844350-00005      Date of last issue: 07.10.2015  
Date of first issue: 26.11.2014

ding site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alterna-	2,500 t	25,000 t

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 07.10.2015
1.4	12.11.2015	844350-00005	Date of first issue: 26.11.2014

---

tive fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

**The components of this product are reported in the following inventories:**

- KECI : All ingredients listed, exempt or notified.
- REACH : All ingredients (pre-)registered or exempt.
- TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
- AICS : All ingredients listed or exempt.
- IECSC : All ingredients listed or exempt.
- ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- PICCS : All ingredients listed or exempt.
- NZIoC : All ingredients listed or exempt.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

#### Full text of H-Statements

- H304 : May be fatal if swallowed and enters airways.
- H315 : Causes skin irritation.
- H318 : Causes serious eye damage.
- H335 : May cause respiratory irritation.

#### Full text of other abbreviations

- Asp. Tox. : Aspiration hazard
- Eye Dam. : Serious eye damage
- Skin Irrit. : Skin irritation
- STOT SE : Specific target organ toxicity - single exposure
- 91/322/EEC : Europe. Commission Directive 91/322/EEC on establishing indicative limit values
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- 91/322/EEC / TWA : Limit Value - eight hours
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 07.10.2015
1.4	12.11.2015	844350-00005	Date of first issue: 26.11.2014

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, in-

## MOLYKOTE(R) G-RAPID PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 07.10.2015
1.4	12.11.2015	844350-00005	Date of first issue: 26.11.2014

---

cluding an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN