



Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-3962-9	Version number:	4.00
Revision date:	26/11/2014	Supersedes date:	10/05/2013
Transportation version number:	1.00 (25/10/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

Product Identification Numbers

GR-2001-2469-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Sensitizing; R43

For full text of R phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING!

Symbols:

GHS07 (Exclamation mark) |

Pictograms



Ingredient	CAS Nbr	% by Wt
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	0.1 - 1
1,2-Benzisothiazol-3(2H)-one	2634-33-5	< 0.1

HAZARD STATEMENTS:

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P260E Do not breathe vapour or spray.
P262 Do not get in eyes, on skin, or on clothing.
P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P331 Do NOT induce vomiting.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

29% of the mixture consists of components of unknown acute oral toxicity.
29% of the mixture consists of components of unknown acute dermal toxicity.
56% of the mixture consists of components of unknown acute inhalation toxicity.
Contains 2% of components with unknown hazards to the aquatic environment.

Notes on labelling

Nota P applied to CAS # 64742-95-6. Nota L applied to CAS # 64742-54-7.
H317 applied due to vendor test data.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)



Irritant

Contains:

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

1,2-Benzisothiazol-3(2H)-one; 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-

Risk phrases

R43 May cause sensitisation by skin contact.

Safety phrases

S23C Do not breathe vapour or spray.
 S51 Use only in well ventilated areas.
 S24 Avoid contact with skin.
 S37 Wear suitable gloves.
 S62 If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label.

Notes on labelling

Nota P applied to CAS# 64742-95-6. Nota L applied to CAS# 64742-54-7.
 R43 based on vendor test data of raw material.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Non-hazardous ingredients	Mixture		60 - 70	
Titanium dioxide	13463-67-7	EINECS 236-675-5	20 - 30	
Synthetic amorphous silica, fumed, crystalline free	112945-52-5		1 - 5	
Solvent naphtha (petroleum), light aromatic	64742-95-6	EINECS 265-199-0	1 - 5	Xn:R65 - Nota 4,P (EU) R10 (Vendor) Xi:R38; R67 (Self Classified) Asp. Tox. 1, H304 - Nota P (CLP) Flam. Liq. 3, H226 (Vendor) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)
2-Butoxyethanol	111-76-2	EINECS 203-905-0	1 - 5	Xn:R20-21-22; Xi:R36-38 (EU) R52 (Self Classified) Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 (CLP)
2-Dimethylaminoethanol	108-01-0	EINECS 203-542-8	< 1	C:R34; Xn:R20-21-22; R10 (EU) Flam. Liq. 3, H226; Acute Tox. 3, H331; Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Corr. 1B, H314; STOT SE 3, H335 (CLP)
Mesitylene	108-67-8	EINECS 203-	< 1	Xi:R37; N:R51/53; R10 (EU)

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

		604-4		Flam. Liq. 3, H226; STOT SE 3, H335; Aquatic Chronic 2, H411 (CLP)
1,2,4-Trimethylbenzene	95-63-6	EINECS 202-436-9	< 1	Xn:R20; Xi:R36-37-38; N:R51/53; R10 (EU) Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 2, H411 (CLP)
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	EINECS 204-809-1	0.1 - 1	R52/53 (Vendor) Xi:R41; R43 (Self Classified) Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 2, H411 (Self Classified)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	EINECS 265-157-1	< 1	Nota L (EU) R66; R67 (Self Classified) Nota L (CLP) EUH066 (Self Classified)
1,2-Benzisothiazol-3(2H)-one	2634-33-5	EINECS 220-120-9	< 0.1	Xn:R22; Xi:R38-41; N:R50; R43 (EU) Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Acute 1, H400,M=10 (CLP) Aquatic Chronic 1, H410,M=10 (Self Classified)
Ammonia, aqueous solution	1336-21-6	EINECS 215-647-6	< 0.1	C:R34; N:R50 - Nota B (EU) Skin Corr. 1B, H314; STOT SE 3, H335; Aquatic Acute 1, H400,M=1 - Nota B (CLP) Met. Corr. 1, H290 (Vendor)
Benzene	71-43-2	EINECS 200-753-7	< 0.1	Carc.Cat.1:R45; Muta.Cat.2:R46; F:R11; T:R48/23; T:R48/24; T:R48/25; Xn:R65; Xi:R36-38 - Nota E (EU) R52 (Self Classified) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Muta. 1B, H340; Carc. 1A, H350; STOT RE 1, H372 (CLP)

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Eliminate all ignition sources if safe to do so. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning: A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-Dimethylaminoethanol	108-01-0	UK HSC	TWA:7.4 mg/m ³ (2 ppm);STEL:22 mg/m ³ (6 ppm)	
2-Butoxyethanol	111-76-2	UK HSC	TWA:123 mg/m ³ (25 ppm);STEL:246 mg/m ³ (50 ppm)	Skin Notation
Titanium dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4 mg/m ³	
Benzene	71-43-2	UK HSC	TWA:3.25 mg/m ³ (1 ppm)	Skin Notation

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
------------	---------	--------	-------------	---------------------	---------------	-------	---------------------

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

2-Butoxyethanol 111-76-2 UK EH40 BMGVs Butoxyacetic acid Creatinine in urine EOS 240 mmol/mol

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)
EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	No data available	No data available
Polymer laminate	No data available	No data available

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Boot covers - Disposable
Coveralls - Disposable, laminate
Apron - polymer laminate
Rubber boots.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Faint musty odour; White colour
Odour threshold	No data available.
pH	8
Boiling point/boiling range	>=100 °C

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	>=65 °C [<i>Test Method</i> :Closed Cup]
Autoignition temperature	415 °C
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<=6,132.8 Pa [<i>@</i> 20 °C]
Relative density	1.31 [<i>Ref Std</i> :WATER=1]
Water solubility	Appreciable
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.31 g/ml

9.2. Other information

Volatile organic compounds (VOC)	110 g/l [<i>Test Method</i> :Estimated] [<i>Details</i> :EU Definition (Part A and B mix)]
Volatile organic compounds (VOC)	99.5 g/l [<i>Test Method</i> :Estimated] [<i>Details</i> :EU Definition (Part A and B mix thinned 10%)]
Percent volatile	40.20 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Accelerators
Alcohols.
Amines.
Strong acids.
Strong bases.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Blood effects: Signs/symptoms may include generalised weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and hemoglobinemia.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE ₂₀ - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD ₅₀ > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC ₅₀ > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD ₅₀ > 10,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Dermal	Rabbit	LD ₅₀ > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Inhalation-Dust/Mist (4 hours)	Rat	LC ₅₀ > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Rat	LD ₅₀ > 5,110 mg/kg
2-Butoxyethanol	Dermal	Rabbit	LD ₅₀ 400 mg/kg

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

2-Butoxyethanol	Inhalation-Vapor (4 hours)	Rat	LC50 2.2 mg/l
2-Butoxyethanol	Ingestion	Rat	LD50 560 mg/kg
Solvent naphtha (petroleum), light aromatic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Solvent naphtha (petroleum), light aromatic	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Solvent naphtha (petroleum), light aromatic	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Dimethylaminoethanol	Dermal	Rabbit	LD50 1,220 mg/kg
2-Dimethylaminoethanol	Inhalation-Vapor (4 hours)	Rat	LC50 6 mg/l
2-Dimethylaminoethanol	Ingestion	Rat	LD50 1,803 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Dermal	Rat	LD50 > 2,000 mg/kg
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Ingestion	Rat	LD50 > 500 mg/kg
Mesitylene	Dermal	Rabbit	LD50 > 3,160 mg/kg
Mesitylene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
Mesitylene	Ingestion	Rat	LD50 3,400 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic	Dermal	Rabbit	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic	Ingestion	Rat	LD50 > 5,000 mg/kg
Ammonia, aqueous solution	Ingestion	Rat	LD50 350 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Titanium dioxide	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Irritant
Solvent naphtha (petroleum), light aromatic	Rabbit	Irritant
2-Dimethylaminoethanol	Rabbit	Corrosive
1,2,4-Trimethylbenzene	Rabbit	Irritant
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Rabbit	No significant irritation
Mesitylene	Rabbit	Irritant
Distillates (petroleum), hydrotreated heavy paraffinic	Rabbit	Minimal irritation
Ammonia, aqueous solution	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Titanium dioxide	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Severe irritant
Solvent naphtha (petroleum), light aromatic	Rabbit	Mild irritant
2-Dimethylaminoethanol	official classification	Corrosive
1,2,4-Trimethylbenzene	Rabbit	Mild irritant
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Rabbit	Corrosive
Mesitylene	Rabbit	Mild irritant
Distillates (petroleum), hydrotreated heavy paraffinic	Rabbit	Mild irritant
Ammonia, aqueous solution	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Titanium dioxide	Human and animal	Not sensitizing
Synthetic amorphous silica, fumed, crystalline free	Human and animal	Not sensitizing

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

2-Butoxyethanol	animal Guinea pig	Not sensitizing
Solvent naphtha (petroleum), light aromatic	Guinea pig	Not sensitizing
2-Dimethylaminoethanol	Mouse	Some positive data exist, but the data are not sufficient for classification
1,2,4-Trimethylbenzene	Guinea pig	Not sensitizing
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	Mouse	Sensitising
Mesitylene	Guinea pig	Not sensitizing
Distillates (petroleum), hydrotreated heavy paraffinic	Guinea pig	Not sensitizing

Respiratory Sensitisation

Name	Species	Value
------	---------	-------

Germ Cell Mutagenicity

Name	Route	Value
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Synthetic amorphous silica, fumed, crystalline free	In Vitro	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Dimethylaminoethanol	In Vitro	Not mutagenic
2-Dimethylaminoethanol	In vivo	Not mutagenic
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic
Mesitylene	In Vitro	Not mutagenic
Distillates (petroleum), hydrotreated heavy paraffinic	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Synthetic amorphous silica, fumed, crystalline free	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Solvent naphtha (petroleum), light aromatic	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated heavy paraffinic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-Butoxyethanol	Dermal	Not toxic to development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Some positive developmental data exist, but the data are not sufficient for	Rat	NOAEL 100 mg/kg/day	during organogenesis

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

		classification			
2-Butoxyethanol	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
Solvent naphtha (petroleum), light aromatic	Inhalation	Not toxic to female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Solvent naphtha (petroleum), light aromatic	Inhalation	Not toxic to male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Solvent naphtha (petroleum), light aromatic	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 500 ppm	2 generation
2-Dimethylaminoethanol	Inhalation	Not toxic to development	Rat	NOAEL 0.3 mg/l	during gestation
2-Dimethylaminoethanol	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	LOAEL 300 mg/kg	during gestation
2-Dimethylaminoethanol	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.13 mg/l	9 days
2-Dimethylaminoethanol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	LOAEL 300 mg/kg/day	during gestation
1,2,4-Trimethylbenzene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.5 mg/l	during gestation
Mesitylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.5 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Butoxyethanol	Dermal	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Inhalation	blood	May cause damage to organs	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

2-Butoxyethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	poisoning and/or abuse
Solvent naphtha (petroleum), light aromatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Solvent naphtha (petroleum), light aromatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Solvent naphtha (petroleum), light aromatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Dimethylaminoethanol	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL 0.09 mg/l	90 days
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Mesitylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Mesitylene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Distillates (petroleum), hydrotreated heavy paraffinic	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Ammonia, aqueous solution	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.010 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure
Synthetic amorphous silica, fumed, crystalline free	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
2-Butoxyethanol	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	All data are negative	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	blood	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.12 mg/l	90 days
2-Butoxyethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for	Multiple animal	NOAEL Not available	not available

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

			classification	species		
2-Dimethylaminoethanol	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.13 mg/l	9 days
2-Dimethylaminoethanol	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.37 mg/l	9 days
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	heart endocrine system immune system	All data are negative	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	14 days
1,2,4-Trimethylbenzene	Ingestion	liver immune system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Mesitylene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
Mesitylene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
Mesitylene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Mesitylene	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Inhalation	heart endocrine system immune system	All data are negative	Rat	NOAEL 1.2 mg/l	3 months
Mesitylene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	14 days
Mesitylene	Ingestion	liver immune system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Distillates (petroleum), hydrotreated heavy paraffinic	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.21 mg/l	28 days

Aspiration Hazard

Name	Value
Solvent naphtha (petroleum), light aromatic	Aspiration hazard
1,2,4-Trimethylbenzene	Aspiration hazard
Mesitylene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
1,2,4-Trimethylbenzene	95-63-6	Mysid Shrimp	Experimental	96 hours	EC50	2 mg/l
1,2,4-Trimethylbenzene	95-63-6	Fathead minnow	Experimental	96 hours	LC50	7.72 mg/l
1,2,4-Trimethylbenzene	95-63-6	Water flea	Experimental	48 hours	EC50	3.6 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Algae	Experimental	72 hours	EC50	0.15 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	4.4 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Crustacea	Experimental	48 hours	EC50	0.062 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	EC50	>1,000 mg/l
2-Butoxyethanol	111-76-2	Crustacea	Experimental	96 hours	EC50	89.4 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	21 days	NOEC	100 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	48 hours	EC50	1,550 mg/l
2-Butoxyethanol	111-76-2	Rainbow trout	Experimental	96 hours	LC50	1,474 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	NOEC	130 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Fathead minnow	Experimental	96 hours	LC50	36 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Green algae	Experimental	72 hours	EC50	82 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Green algae	Experimental	72 hours	NOEC	1 mg/l
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Water flea	Experimental	48 hours	EC50	88 mg/l
Ammonia,	1336-21-6	Algae or other	Experimental	72 hours	NOEC	0.73 mg/l

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

aqueous solution		aquatic plants				
Ammonia, aqueous solution	1336-21-6	Water flea	Experimental	21 days	NOEC	18.6 mg/l
Ammonia, aqueous solution	1336-21-6	Algae or other aquatic plants	Experimental	72 hours	IC50	10.4 mg/l
Ammonia, aqueous solution	1336-21-6	Fish	Experimental	96 hours	LC50	1.7 mg/l
Ammonia, aqueous solution	1336-21-6	Grass Shrimp	Experimental	48 hours	EC50	9.69 mg/l
Ammonia, aqueous solution	1336-21-6	Bluegill	Experimental	32 days	NOEC	1.56 mg/l
Benzene	71-43-2	Water flea	Experimental	48 hours	EC50	9.23 mg/l
Benzene	71-43-2	Green Algae	Experimental	72 hours	EC50	29 mg/l
Benzene	71-43-2	Rainbow trout	Experimental	96 hours	LC50	5.3 mg/l
2-Dimethylamin oethanol	108-01-0	Fathead minnow	Experimental	96 hours	LC50	81 mg/l
2-Dimethylamin oethanol	108-01-0	Water flea	Experimental	48 hours	EC50	99 mg/l
2-Dimethylamin oethanol	108-01-0	Green algae	Experimental	72 hours	EC50	35 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7		Data not available or insufficient for classification			
Solvent naphtha (petroleum), light aromatic	64742-95-6		Data not available or insufficient for classification			
Mesitylene	108-67-8	Ricefish	Experimental	48 hours	LC50	8.6 mg/l
Mesitylene	108-67-8	Water flea	Experimental	48 hours	EC50	6 mg/l
Mesitylene	108-67-8	Green algae	Experimental	48 hours	EC50	53 mg/l
Mesitylene	108-67-8	Water flea	Experimental	21 days	NOEC	0.4 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Water flea	Experimental	24 hours	EC50	>100 mg/l

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green Algae	Experimental	72 hours	NOEC	60 mg/l
Titanium dioxide	13463-67-7	Sheepshead Minnow	Experimental	96 hours	LC50	>240 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	30 days	NOEC	3 mg/l
Titanium dioxide	13463-67-7	Fish	Experimental	30 days	NOEC	>100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
1,2,4-Trimethylbenzene	95-63-6	Experimental Photolysis		Photolytic half-life (in air)	11.8 hours (t 1/2)	Other methods
Ammonia, aqueous solution	1336-21-6	Experimental Photolysis		Photolytic half-life (in air)	201 days (t 1/2)	Other methods
Benzene	71-43-2	Experimental Photolysis		Photolytic half-life (in air)	26.1 days (t 1/2)	Other methods
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	64742-95-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Dimethylaminoethanol	108-01-0	Experimental Biodegradation	14 days	BOD	60.5 % weight	OECD 301C - MITI test (I)
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
Mesitylene	108-67-8	Experimental Biodegradation	14 days	BOD	0 % weight	OECD 301C - MITI test (I)
1,2,4-Trimethylbenzene	95-63-6	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301C - MITI test (I)
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Experimental Biodegradation	28 days	CO2 evolution	5 % weight	OECD 301B - Modified Sturm or CO2
2-Butoxyethanol	111-76-2	Experimental Biodegradation	14 days	BOD	96 % weight	OECD 301C - MITI test (I)
Distillates (petroleum), hydrotreated	64742-54-7	Data not available or insufficient for	N/A	N/A	N/A	N/A

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

heavy paraffinic		classification				
Benzene	71-43-2	Experimental Biodegradation	28 days	BOD	63 % weight	OECD 301F - Manometric respirometry

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	64742-95-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mesitylene	108-67-8	Experimental BCF-Carp	70 days	Bioaccumulation factor	342	Other methods
1,2,4-Trimethylbenzene	95-63-6	Experimental BCF-Carp	56 days	Bioaccumulation factor	275	Other methods
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	Experimental Bioconcentration		Log Kow	2.8	Other methods
Benzene	71-43-2	Experimental BCF - Other		Bioaccumulation factor	4.26	Other methods
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods
2-Dimethylaminoethanol	108-01-0	Experimental Bioconcentration		Log Kow	-0.55	Other methods
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	Other methods
Ammonia, aqueous solution	1336-21-6	Experimental Bioconcentration		Log Kow	-1.14	Other methods
2-Butoxyethanol	111-76-2	Experimental Bioconcentration		Log Kow	0.83	Other methods
Benzene	71-43-2	Experimental Bioconcentration		Log Kow	2.13	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

3M Scotchkote Urethane Wall Coating UV 843 20%, White (Part A)

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

GR-2001-2469-5

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2-Butoxyethanol	111-76-2	Gr. 3: Not classifiable	International Agency for Research on Cancer Regulation (EC) No. 1272/2008, Table 3.1
Benzene	71-43-2	Carc. 1A	International Agency for Research on Cancer Regulation (EC) No. 1272/2008, Table 3.2
Benzene	71-43-2	Carc.Cat.1	International Agency for Research on Cancer Regulation (EC) No. 1272/2008, Table 3.2
Benzene	71-43-2	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer Regulation (EC) No. 1272/2008, Table 3.2
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer Regulation (EC) No. 1272/2008, Table 3.2

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

List of relevant R-phrases

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R21	Harmful in contact with skin.
R22	Harmful if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R45	May cause cancer.
R46	May cause heritable genetic damage.
R48/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
R48/24	Toxic: danger of serious damage to health by prolonged exposure in contact with skin.
R48/25	Toxic: danger of serious damage to health by prolonged exposure if swallowed.
R50	Very toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R52	Harmful to aquatic organisms.
R52/53	Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R65	Harmful: May cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Revision information:

Revision Changes:

Safety phrase information was modified.

Section 8: Personal Protection - Skin/body information information was modified.

Section 1: Product identification numbers heading information was modified.

Section 16: List of relevant R phrase information information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Copyright information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Telephone header information was modified.

Company Telephone information was modified.

Section 11: Aspiration Hazard Table information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 11: Health Effects - Inhalation information information was modified.

Section 5: Fire - Extinguishing media information information was modified.

Section 6: Accidental release clean-up information information was modified.

Section 7: Precautions safe handling information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Personal Protection - Eye information information was modified.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 8: Personal Protection - Respiratory Information information was modified.

Section 13: 13.1. Waste disposal note information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Section 2: Label ingredient information information was added.

Section 12: Component ecotoxicity information information was added.

Section 12: Persistence and Degradability information information was added.

Section 12:Biocummulative potential information information was added.

Section 12: Component Ecotoxicity table Material column header information was added.

Section 12: Component Ecotoxicity table CAS No column header information was added.

Section 12: Component Ecotoxicity table Organism column header information was added.

Section 12: Component Ecotoxicity table Type column header information was added.

Section 12: Component Ecotoxicity table Exposure column header information was added.

Section 12: Component Ecotoxicity table End point column header information was added.

Section 12: Component Ecotoxicity table Result column header information was added.

Section 12: Persistence and degradability table Material column header information was added.

Section 12: Persistence and degradability table CAS No column header information was added.

Section 12: Persistence and degradability table Test Type column header information was added.

Section 12: Persistence and degradability table Duration column header information was added.

Section 12: Persistence and degradability table Test Result column header information was added.

Section 12: Persistence and degradability table Protocol column header information was added.

Section 12:Biocummulative potential table Material column header information was added.

Section 12:Biocummulative potential table CAS No column header information was added.

Section 12:Biocummulative potential table CAS No column header information was added.

Section 12:Biocummulative potential table Test Result column header information was added.

Section 12:Biocummulative potential table Protocol column header information was added.

Section 12:Biocumulative potential table Test Type column header information was added.
Label: Signal Word - Header information was added.
Label: Signal Word information was added.
Label: CLP Classification - Header information was added.
Label: CLP Classification information was added.
Label: CLP Classification information was added.
Label: CLP Classification - Header information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Percent Unknown information was added.
Label: Graphic information was added.
Label: Graphic information was added.
Label: Symbol information was added.
Label: Symbol information was added.
Label: CLP Precautionary - Prevention information was added.
Label: CLP Precautionary - Prevention - Header information was added.
Label: CLP Precautionary - Response information was added.
Label: CLP Precautionary - Response - Header information was added.
Label: Precautionary Statement - Header information was added.
CLP: Ingredient table information was added.
Section 2: Notes on labelling heading information was added.
Section 15: Label remarks and EU Detergent information was added.
Section 8: Occupational exposure limit table information was added.
Section 11: Carcinogenicity heading information was added.
Section 11: Cancer Hazards information information was added.
Section 2: 2.2 & 2.3. CLP REGULATION heading information was added.
Label: CLP Ingredients table Ingredient heading information was added.
Label: CLP Ingredients table CAS No heading information was added.
Label: CLP Ingredients table Percent by Wt heading information was added.
Section 12: Persistence and degradability table Study Type column header information was added.
Section 12:Biocumulative potential table Test Type column header information was added.
Section 2: H phrase reference information was added.
Legend description information was added.
BLV Reg Agency Desc information was added.
Section 10: Hazardous decomposition products during combustion text information was added.
Section 11: Disclosed components not in tables text information was added.
Section 12: Classification Warning information was added.
Section 11: Classification disclaimer information was added.
Section 8: 8.1.1 Biological limit values table heading information was added.
Section 8: BLV table information was added.
Section 8: BLV table ingredient column heading information was added.
Section 8: BLV table cas nbr column heading information was added.
Section 8: BLV table agency column heading information was added.
Section 8: BLV table cas nbr column heading information was added.
Section 8: BLV table biological specimen Column heading information was added.
Section 8: BLV table sampling time Column heading information was added.
Section 8: BLV table value Column heading information was added.
Section 8: BLV table additional comments Column heading information was added.
Section 8: glove data - Material heading information was added.
Section 8: glove data - Thickness heading information was added.
Section 8: glove data - Breakthrough Time heading information was added.
Section 8: glove data value information was added.
Section 8: Skin protection - recommended gloves information information was deleted.
Section 8: Eye/face protection text information was deleted.
Section 8: Respiratory protection - recommended respirators information was deleted.

Section 2: Label ingredient information information was deleted.
Section 12: Acute aquatic hazard information information was deleted.
Section 12: Chronic aquatic hazard heading information was deleted.
Section 12: Acute aquatic hazard heading information was deleted.
Section 12: Chronic aquatic hazard information information was deleted.
Prints No Data if Component ecotoxicity information is not present information was deleted.
Prints No Data if Persistence and Degradability information is not present information was deleted.
Prints No Data if Bioaccumulative potential information is not present information was deleted.
Section 8: mg/m³ key information was deleted.
Section 8: ppm key information was deleted.
Section 11: Classification disclaimer information was deleted.
Section 11: Respiratory Sensitization Table information was deleted.
Section 12: Classification Warning information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk